



www.lubegard.com



69032 >>



COMPLETE™ Full Synthetic Automatic Transmission Fluid

WITH LXE® TECHNOLOGY

LUBEGARD® COMPLETE™ Full Synthetic ATF is a world-class lubricant formulated for outstanding performance and efficiency in meeting or exceeding OEM requirement for reduced viscosity.

Lubegard's unique, proprietary LXE® Technology provides superior wear protection with improved frictional and shear stability (high film strength for the life of the fluid).

This unique technology prevents and eliminates torque converter shudder, improves shift quality and imparts excellent torque carrying capacity for long clutch and component life. LXE® Technology is seal and o-ring friendly, ideal for new, older, and higher-mileage vehicles.

Lubegard® COMPLETE™ Full Synthetic ATF is recommended for all automatic transmissions that require a fully formulated low viscosity ATF with exceptional performance and uncompromising protection. It is engineered to meet or exceed OEM requirements where lower viscosity is required.

BENEFITS:

- >> World class replacement for synthetic low viscosity ATF such as Dexron VI & HP, Mercon LV, Toyota WS.
- >> Backward compatible to replace DEXRON® fluids in older automatic transmissions that call for DEXRON® as well as Honda applications that call for Z-1® ATF.
- >> Formulated with LXE® Technology to meet OEM requirements for shear stability, long term frictional stability, superior shift quality and anti-shudder properties.
- >> Seal-friendly LXE® Technology restores seal flexibility and performance to older and high mileage transmissions.
- >> Cures sluggish transmission performance on cold mornings.
- >> The #1 technology used and endorsed by transmission shops for over 30 years now available as a world class service solution for automatic transmissions.

AVAILABILITY:

Stock No.	Unit Size	Case/Qnty
69032	32 oz. (946 mL)	6/c
69125	1.25gal	3/c
69055	55 gal.	n/a
69330	330 gal. tote	n/a

SEE BACK FOR A COMPLETE LISTING OF COMPATIBLE ATFs

TYPICAL PROPERTIES:

PROPERTY	ASTM TEST METHOD	DATA
Viscosity @ 40° C, cSt	D445	29.50
Viscosity @ 100° C, cSt	D445	6.00
Viscosity Index	D2270	155
Flash Point, COC, °C (°F)	D92	208 (406)
Pour Point, °C (°F)	D5949/5950/6892	-48 (-54)
Color	D1500	Red



LUBEGARD COMPLETE™ Full Synthetic Transmission Fluid is suitable for use with the following ATFs:

Aisin

M315
AW-1

Allison C-4

Audi/Volkswagen

Esso Type LT 71141 G 052 162
G 052 990 A2
G 055 005 A2
G 055 162 A2 or A6
G 055 540 A2
G 060 162 A2
GUS 00 162

BMW

83 22 2 163 514
83 22 2 152 426, Shell
M-L12108
83 22 2 355 599, BMW ATF6
83 22 2 413 477, BMW ATF7
83 22 0 026 922,
Texaco ETL-7045 E
83 22 0 024 359,
Texaco ETL-8072 B
83 22 0 142 516
83 22 0 397 114
83 22 9 400 272
83 22 9 400 275
83 22 0 403 249
83 22 9 407 765
83 22 9 407 807
83 22 9 407 858
83 22 9 407 859

Chrysler/Dodge/Ram

Mopar ASRC ATF
(previously AS68RC ATF)
05127382AA
Shell L12108
Mopar ZF 8 & 9 Speed ATF,
P/N 68218925AB

Daewoo

LT 711141

Daihatsu

Alumix Multi

Fiat

Mopar AW-1
Mopar Long Life Fluid P/N
68333587AA

Ford

Mercon SP
Mercon LV
Motorcraft FNR5 ATF,
P/N XT-9-QMM5

GM

DEXRON -III-H
DEXRON-VI
GM P/N 19256039, AW-1
DEXRON HP
12378515
Mobil 1 Synthetic LV
ATF HP

Honda/Acura

ATF DW-1 Fluid
Honda ATF-Z
Acura/Honda ATF Type 3.1

Hyundai

SP-II, SP-III, SP-IV
Hyundai NWS 9638
Hyundai Apollo ATF
Red 1K

Infiniti

Matic D
Matic J
Matic K
Matic S

Isuzu

Isuzu Genuine ATF, P/N
2-90531-2000 (AISIN SCS
T-4 ATF)
Isuzu Besco ATF-II, III

Jaguar

JLM 20238 (LT 711141)
Idemitsu K17
8342

Jeep

Mopar ZF 8 & 9 Speed ATF
SK ATF SPIV

Kia

SP-II, SP-III, SP-IV, SP-VI
Kia Red 1, P/N UM040
CH020 or Appolloil ATF
RED-1K
Kia SP-IV-RR
Kia SK ATF SP4M-1,
Michang ATF SP4M-1,
NOCA ATF SP4M-1

Land Rover

AW-1, Land Rover P/N
LR0022460
Texaco N402
LT 71141
Shell 1375.4

Lexus

World Standard

Mazda

ATF M-V
Mazda ATF M-3
0000-77-122E-01

Mercedes

MB 001 989 21 03-10
MB 001 989 68 03-10
MB Sheet 236.1
MB Sheet 236.2
MB Sheet 236.5
MB Sheet 236.6
MB Sheet 236.7
MB Sheet 236.8
MB Sheet 236.9
MB Sheet 236.10
MB Sheet 236.12
MB Sheet 236.13
MB Sheet 236.14
MB Sheet 236.15
MB Sheet 236.16
MB Sheet 236.41
MB Sheet 236.81

Mini

83 22 2 355 599, BMW ATF6

Mitsubishi

Diamond ATF SP-II, SP-III
Dia Queen ATF-J2, J3

Nissan

Nissan Matic D
Nissan Matic J

Nissan Matic K
Nissan Matic S
Nissan Matic W

Porsche

000 043 304 00
958 300 540 00
Shell M-L12108,
P/N 000 043 210 54

Saab

93 165 146
93 165 147
Saab Aporoil

Saturn

21005966

Scion

World Standard (WS)

Subaru

Subaru ATF HP
K0140Y0700
SOA868V9241

Suzuki

Suzuki Matic J
Suzuki Matic S

Toyota

World Standard (WS)

Volvo

AW-1, P/N 31256 774
1161521
1161641
97340
97341

All trademarks are property of their respective owners.

***IF THE VEHICLE IS UNDER WARRANTY, BE SURE TO USE FLUID THAT IS THE SAME COLOR AS OEM'S.**